

UTV500

Specifications

ENGINE:

Type: 471CC, Water cooled, 4-Stroke, 1-Cylinder

Bore X Stroke(inch): 3.33"x3.31"

Compression Ratio: 9.4:1

Max.Power: 22.8HP/5500rpm

Max.Torque: 19.6FT/lbs/4000rpm

Fuel Supply: Electric Fuel Inject

Ignition: ECU

Starting: Electric

Transmission: L-H-N-R-P

Drive Train: Axle

CHASSIS:

Suspension/Front: Independent double swing arm

Suspension/Rear: Independent double swing arm

Brakes/Front: Dual ventilated hydraulic disc

Brakes/Rear: Ventilasted hydraulic disc

Tires/Front: AT26 x 9-12 radial

Tires/Rear: AT26 x10-12 radial

DIMENSIONS:

LxWxH(inch): 98.8"x47.9"x60.4"

Seat Height(inch): 26"

Wheelbase(inch): 62"

Ground Clearance(inch): 96.5"

Fuel Capacity: 29L/7.7Gal

Dry Weight: 1128lbs

Light: 12V35W/35Wx2, 12V5Wx2(Front), 12V5W/21Wx1(Rear)

Loading: 4pc/20'GP, 9pc/40'GP, 18pc/40'HQ

Colors:



Features

4 wheel drive - Dump Cargo Bed - Electric Fuel Inject - Remote Winch
Latching Side Doors - Digital Speedometer Display - Rear Hitch Receiver

Accessories

Suntop - 3 types of Windshields - Winch - Aluminum Rims - Storage Console
3 types of Snow Plows - Turn Signals - Mirrors - Large Tread Tires