

UTV700-4

Specifications

Engine: 4 Stroke, liquid cooled, 1 cylinder

Displacement: 686cc

Bore x Stroke: 102mm x 84mm

Compression Ratio: 9.1:1

Max Power: 33.5 hp/5000-5500rpm

Max Torque: 30.5ft/bs / 4000rpm

Fuel Supply: Electric Fuel Inject

Ignition: ECU

Start Type: Electric

Transmission: L-H-N-R-P

Drive System: Axle, 2/4wd + Diff Lock

Suspension Front:

Independent double swing arm

Suspension Rear:

Independent double swing arm

Brakes Front:

Dual ventilated hydraulic disk

Brakes Rear:

Ventilated hydraulic disk

Dimensions (LxWxH):

155x56.3x75 inches

Wheel Base: 113 inches

Seat Height: 32 inches

Ground Clearance: 12 inches

Fuel Capacity: 7.8 gallons

Dry Weight: 1472 pounds

Battery: 12V/21Ah

Lights Front: 12v35w/35w x 2, 12v5w x 2

Lights Rear: 12v.5w/21w x 1

Tires Front: AT26 x 9-12

Tires Rear: AT26 x 10-12

Shipping Qty: 11 (40ft HQ)

Available Colors:



Features

4 wheel drive - Dump Cargo Bed - Fuel Injected - Remote Winch

Latching Side Doors - Digital Speedometer Display - Rear Hitch Receiver

Accessories

Suntop - 3 types of Windshields - Winch - Aluminum Rims - Storage Console

3 types of Snow Plows - Turn Signals - Mirrors - Large Tread Tires



US TITAN INC
SUPERMACH POWERSPORTS
1-866-399-9997

DEALER INFO: