WWW. SUPERMACH .COM

MOPEDS - ATVS - DIRT BIKES - UTVS

UTV700

Specifications

Engine: 4 Stroke, liquid cooled, 1 cylinder

Displacement: 686cc

Bore x Stroke: 102mm x 84mm Compression Ratio: 9.1:1

Max Power: 33.5 hp/ 5000-5500rpm Max Torque: 30.5ft/bs / 4000rpm Fuel Supply: Electric Fuel Inject

Ignition: ECU

Start Type: Electric / Pull Start Transmission: L-H-N-R-P

Drive System: Axle, 2/4wd, Diff Lock

Suspension Front:

Independent double swing arm

Suspension Rear:

Independent double swing arm

Brakes Front:

Dual ventilated hydraulic disk

Brakes Rear:

Ventilated hydraulic disk **Dimensions (LxWxH):** 118x56.3x74.8 inches

Wheel Base: 75 inches Seat Height: 32 inches Ground Clearance: 12 inches Fuel Capacity: 7.8 gallons Dry Weight: 1152 pounds

Battery: 12V/21Ah

Lights Front: 12v35w/35w x 2, 12v5w x 2

Lights Rear: 12v.5w/21w x 1 Tires Front: AT26 x 9-12 Tires Rear: AT26 x10-12 Shipping Qty: 22 (53ft Truck)

Available Colors:



4 wheel drive + Diff Lock - Dump Cargo Bed - Fuel Injected - Remote Winch Latching Side Doors - Digital Speedometer Display - Rear Hitch Receiver

Accessories

Suntop - 3 types of Windshields - Winch - Aluminum Rims - Storage Console 3 types of Snow Plows - Turn Signals - Mirrors - Large Tread Tires





DEALER INFO: